

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 21233A9

Issue date: 12/15/2015 Revision date: 7/25/2024 Version: 1.0

## **SECTION 1: Identification**

#### 1.1. Identification

Product form : Substance

2,2-Difluoroethyl difluoroacetate Substance name

CAS-No. 1300698-74-1 Product code : 2123-3-A9 : C4H4F4O2 Formula Other means of identification : MFCD18074351

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

#### 1.3. Supplier

SynQuest Laboratories, Inc. Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615

United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

#### 1.4. Emergency telephone number

: (844) 523-4086 (3E Company - Account 10069) Emergency number

## **SECTION 2: Hazard(s) identification**

## 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flammable liquids Category 2 H225 Highly flammable liquid and vapor

Skin corrosion/irritation Category 1B Causes severe skin burns and eye damage H314

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Specific target organ toxicity - Single exposure, Category 3, May cause respiratory irritation H335

Respiratory tract irritation

Full text of H statements: see section 16

## 2.2. GHS Label elements, including precautionary statements

# **GHS US labeling**

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

No additional information available

#### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
2,2-Difluoroethyl difluoroacetate (Main constituent)	CAS-No.: 1300698- 74-1	≤ 100	Flam. Liq. 2, H225 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

#### **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

7/25/2024 (Revision date) EN (English US) 2/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth

out with water. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media

appropriate for surrounding fire.

## 5.2. Specific hazards arising from the chemical

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.

Explosion hazard : Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers. May form flammable/explosive vapor-air mixture.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.

# 6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

# 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

## 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

7/25/2024 (Revision date) EN (English US) 3/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.3. Methods and material for containment and cleaning up

For containment : S

: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up : Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-

proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into

appropriate container for disposal. Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

#### 6.4. Reference to other sections

No additional information available

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Additional hazards when processed Precautions for safe handling

- : Handle empty containers with care because residual vapors are flammable.
- : Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Keep away from ignition sources.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

No additional information available

## 8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### 8.3. Individual protection measures/Personal protective equipment

## Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

#### Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

## Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

7/25/2024 (Revision date) EN (English US) 4/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Personal protective equipment symbol(s):









#### Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid

No data available Color Odor : No data available : No data available Odor threshold рΗ : No data available Melting point : No data available Freezing point : No data available Boiling point : No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available Molecular mass : 160.07 g/mol Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available No data available Viscosity, kinematic No data available Viscosity, dynamic **Explosion limits** No data available

# 9.2. Other information

Explosive properties

Oxidizing properties

No additional information available

# SECTION 10: Stability and reactivity

# 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

# 10.3. Possibility of hazardous reactions

No additional information available

## 10.4. Conditions to avoid

Keep away from heat, sparks and flame.

7/25/2024 (Revision date) EN (English US) 5/10

No data available

No data available

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 10.5. Incompatible materials

Strong bases. Strong oxidizing agents.

# 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

No additional information available

# 12.2. Persistence and degradability

### 2,2-Difluoroethyl difluoroacetate (1300698-74-1)

Persistence and degradability Rapidly degradable

# 12.3. Bioaccumulative potential

No additional information available

# 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

7/25/2024 (Revision date) EN (English US) 6/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

## **SECTION 14: Transport information**

#### 14.1. UN number

Not regulated for transport

## 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, corrosive, n.o.s.

Proper Shipping Name (TDG) : Not applicable

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, CORROSIVE, N.O.S.

Proper Shipping Name (IATA) : Flammable liquid, corrosive, n.o.s.

## 14.3. Transport hazard class(es)

#### **DOT**

Transport hazard class(es) (DOT) : 3 (8) Hazard labels (DOT) : 3, 8





#### **TDG**

Transport hazard class(es) (TDG) : Not applicable

#### **IMDG**

Transport hazard class(es) (IMDG) : 3 (8) Hazard labels (IMDG) : 3, 8





#### **IATA**

Transport hazard class(es) (IATA) : 3 (8) Hazard labels (IATA) : 3, 8





## 14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : Not applicable

Packing group (IMDG) : II
Packing group (IATA) : II

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

**DOT** 

UN-No.(DOT) : UN2924

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59

F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 243
DOT Quantity Limitations Passenger aircraft/rail (49 : 1 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

**DOT Vessel Stowage Location** 

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

: 5 L

**TDG** 

No data available

**IMDG** 

Special provision (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T11
Tank special provisions (IMDG) : TP2, TP2

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-C - SPILLAGE SCHEDULE Charlie - FLAMMABLE CORROSIVE LIQUIDS

Stowage category (IMDG) : B

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y340
PCA limited quantity max net quantity (IATA) : 0.5L
PCA packing instructions (IATA) : 352
PCA max net quantity (IATA) : 1L
CAO packing instructions (IATA) : 363

7/25/2024 (Revision date) EN (English US) 8/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CAO max net quantity (IATA) : 5L
Special provision (IATA) : A3, A803
ERG code (IATA) : 3CH

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

2,2-Difluoroethyl difluoroacetate CAS-No. 1300698-74-1 100%

#### 15.2. International regulations

#### **CANADA**

No additional information available

#### **EU-Regulations**

No additional information available

#### **National regulations**

No additional information available

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

# **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 7/25/2024

Full text of H-phrases		
H225	Highly flammable liquid and vapor	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or

permanent injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can

be ignited under almost all ambient temperature conditions.

: 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

NFPA reactivity

Health : 2 Moderate Hazard - Temporary or minor injury may occur

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.